

01/05/99  
JCS20 U.S. PTO

## APPLICATION TRANSMITTAL

JCS18 U.S. PTO  
09/225189  
01/05/99

Assistant Commissioner  
of Patents  
Washington, DC 20231

Dear Sir,

Transmitted herewith is the below-titled patent  
application.

**MAILING CERTIFICATE:**

I hereby certify that the above correspondence is  
being deposited with the US Postal Service as  
Express Mail, Receipt Number: EJ503420495  
addressed to: Assistant Commissioner for Patents,  
Washington, DC 20231 on the below date.

Julie L. Reed  
Julie L. Reed, Reg. No. 35,349

1/5/99  
Date

Inventors: Qian, Richard J.

Title: "METHOD OF IMAGE BACKGROUND REPLACEMENT"

Attorney Docket No.: SLA0095

No. of pages/sheets:

Application: 12 Informal Drawings: 1

Oath and Declaration: 1

The fee is calculated as follows:

Independent claims	Total claims	Fee
1 - 3 included = 0 extra	10 - 20 included = 0 extra	\$760.00

The Commissioner is hereby authorized to charge indicated fees and credit any  
over payment to:

Deposit Account 50-0803 in the name of Sharp Laboratories of America.

This form is submitted in triplicate.

Respectfully submitted,

Sharp Laboratories, Incorporated  
5750 NW Pacific Rim Blvd.  
Camas, WA 98607  
(360)817-7651

Julie L. Reed  
Julie L. Reed  
Reg. No. 35,349

09225189 010599

# METHOD OF IMAGE BACKGROUND REPLACEMENT

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

This invention relates to image processing for image capture systems,  
5 more particularly to replacing backgrounds in captured images.

### 2. Background of the Invention

New applications for video technology are appearing every day. Video  
conferencing has become commonplace, users can easily download video clips  
from the Internet, and camcorders are inexpensive and widely used. As more of  
10 these applications develop, the ability to edit and change the nature of the  
images becomes more important.

One editing tool that remains unavailable to most of these applications is  
background replacement. Typically, background replacement occurs on video  
images filmed in front of a blue screen. The foreground and background pixels  
15 are easily identified and the new background is put in place using computers or  
specially designed video devices. However, for most people, filming or capturing  
images in front of a blue screen is impractical.

The blue screen process is expensive and inconvenient. A special studio  
for video conferencing restricts the availability of video conferencing facilities and  
20 requires extra cost. Most people publishing on the Internet would find use of a  
blue screen prohibitive, as would most typical users of camcorders. However, all  
of these applications can benefit from background replacement. People video  
conferencing could replace the background of their office with a background for

reasons of privacy, security or aesthetics. Internet publishers could insert  
· images into Web pages more seamlessly, without use of backgrounds or sets.

Camcorder users could record videos and edit the backgrounds at home.

Therefore, a less expensive and more easily accessible technique for  
5 background replacement is needed.

SECRET

## SUMMARY OF THE INVENTION

One embodiment of the invention is a technique for background replacement. The input image or images are analyzed and a preliminary classification of the pixels is made. The classification identifies whether the pixels are more likely foreground or background. After the preliminary classification is made, a more refined process is applied that makes the final determination. Finally, the new background pixels are applied to the image, replacing the previous background pixels. The new image is composed with feathering to ensure smooth edges and transitions. The new image is then output for viewing.

It is an advantage of the invention in that it allows background replacement with no extra equipment or special settings.

It is an advantage of the invention in that it provides background replacement quickly, allowing real-time processing.

It is an advantage of the invention in that it is able to adjust for camera exposure changes and accurate in determining background pixels from foreground pixels.

## BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and for further advantages thereof, reference is now made to the following Detailed Description taken in conjunction with the accompanying Drawings in which:

- 5        Figure 1 shows a process for video background replacement in accordance with the invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

One embodiment of a process for video background replacement is shown in Figure 1. An input device in 10 is used to capture images. Devices such as these include digital cameras, camcorders, film cameras, video conferencing cameras, etc. In step 10 the current background is recorded without any foreground object or objects.

The device 10 then takes incoming frames or an incoming frame of the image with the foreground objects as the input image in step 12. For digital cameras, the input image would be that one image captured by the image input device. The input devices that are video images may capture one or more frames to use as the input image or in the input image analysis.

The input image is then analyzed using a probability function that measures the likelihood of the pixel being foreground or background. One example of such a probability function is:

$$P(\mathbf{p}_{x,y} \in \text{Foreground}) = \begin{cases} \Phi(a \cdot \sqrt{(r_{x,y} - r'_{x,y})^2 + (g_{x,y} - g'_{x,y})^2} + b \cdot |I_{x,y} - I'_{x,y}| + c) & \text{if } I_{x,y} > \eta \\ \Phi(d \cdot |I_{x,y} - I'_{x,y}| + f) & \text{else} \end{cases}$$

and

$$\Phi(u) = \min(\max(0.5 + \text{sign}(u) \cdot u^2, 0), 1)$$

where  $r$  and  $g$  are the chromatic components and  $I$  is the intensity of the pixel  $\mathbf{p}$ ;  $r'$ ,  $g'$  and  $I'$  are their counter parts of pixel  $\mathbf{p}'$  in the pre-recorded background image, and  $a$ ,  $b$ ,  $c$ ,  $d$ ,  $f$ , and  $\eta$  are constants. The values of these constants are tuned by experiments to determine their optimal values.

It is not necessary to restrict this process to chromatic or normalized RGB color space. Use of  $YC_bC_r$  is also possible. In the  $YC_bC_r$  example, the same formulas would be used, with the substitutions of Y for I,  $C_b$  for g and  $C_r$  for r.

Regardless of the color space used for determining the preliminary  
5 classification of a pixel, a probability map is generated that indicates the likelihood of a pixel being foreground or background. The probability map produces a value of a pixel between 0 and 1, where 0 is the foreground and 1 is the background in this particular example. These probabilities could have a threshold applied that would segment the pixels into either the foreground or  
10 background. However, this may lead to false classifications because of ambiguity in certain regions in foreground objects and the background.

Therefore, it is desirable to refine the classification result by utilizing certain context information in space. One may apply morphological filtering to eliminate isolated mis-classified pixels. Other techniques are also available for  
15 this post-processing refinement in step 16. One such technique is anisotropic diffusion, which is discussed below.

Anisotropic diffusion encourages smoothing within boundaries and discourages smoothing across boundaries. In this example, the following anisotropic diffusion equation will be used:

20 
$$P_t = \text{div}(c(x, y, t) \nabla P) = c(x, y, t) \Delta P + \nabla c \cdot \nabla P,$$

where  $\text{div}$  denotes the divergence operator, and  $\nabla$  and  $\Delta$  denote the gradient and Laplacian operators, respectively, with respect to the space variables. The

continuous diffusion equation may be discretized on a square lattice. Using a 4-nearest-neighbors discretization of the Laplacian operator, the equation becomes:

$$5 \quad P_{x,y}^{t+1} = P_{x,y}^t + \lambda [c_N \cdot \nabla_N P + c_S \cdot \nabla_S P + c_E \cdot \nabla_E P + c_W \cdot \nabla_W P]_{x,y}^t$$

and

$$\begin{aligned} \nabla_N P_{x,y} &= P_{x,y-1} - P_{x,y} \\ 10 \quad \nabla_S P_{x,y} &= P_{x,y+1} - P_{x,y} \\ \nabla_E P_{x,y} &= P_{x+1,y} - P_{x,y} \\ \nabla_W P_{x,y} &= P_{x-1,y} - P_{x,y} \end{aligned}$$

where  $0 \leq \lambda \leq 1/4$  for numeric stability reason,  $N, S, E, W$  denote North, South, East and West, respectively. The conduction coefficients  $c_N, c_S, c_E, c_W$  may be computed as follows:

$$\begin{aligned} c_{N_{x,y}} &= g(|\nabla_N I_{x,y}|) \\ c_{S_{x,y}} &= g(|\nabla_S I_{x,y}|) \\ c_{E_{x,y}} &= g(|\nabla_E I_{x,y}|) \\ 20 \quad c_{W_{x,y}} &= g(|\nabla_W I_{x,y}|) \end{aligned}$$

and

$$25 \quad g(|\nabla I|) = \frac{1}{1 + (|\nabla I|/K)^2}$$

where  $K$  is a constant, e.g.,  $K = 1000$ .

This refined probability map from step 16 is then used to overlay foreground pixels on a new background. Some type of blending or feathering



process should be used. Feathering as used here denotes any kind of process that does not just overlay the pixels with no comparison whatsoever between the foreground and background. Specifically, in this example, a weighted average over the pixel value of the input image and the pixel value of the new background is applied. The weights are determined by the probability value from the probability map.

The example of this feathering algorithm for a given location (x,y) in the output image, has the following formulas:

$$\begin{aligned}
 R_{x,y}^{output} &= P(\mathbf{p}_{x,y} \in \text{Foreground}) \cdot R_{x,y}^{input} + (1 - P(\mathbf{p}_{x,y} \in \text{Foreground})) \cdot R_{x,y}^{new\ background} \\
 G_{x,y}^{output} &= P(\mathbf{p}_{x,y} \in \text{Foreground}) \cdot G_{x,y}^{input} + (1 - P(\mathbf{p}_{x,y} \in \text{Foreground})) \cdot G_{x,y}^{new\ background} \\
 B_{x,y}^{output} &= P(\mathbf{p}_{x,y} \in \text{Foreground}) \cdot B_{x,y}^{input} + (1 - P(\mathbf{p}_{x,y} \in \text{Foreground})) \cdot B_{x,y}^{new\ background} .
 \end{aligned}$$

Once the feathering is complete in step 18, the output image with the new background is produced. While the input may be a video image, this technique can be used for printed output as well, such as paper, postcards, photographic paper, etc.

Several modifications of this process are possible. As mentioned previously, the above example relies upon RGB color space for discussion purposes. Other types of processing, including YCbCr, can be used. The selection of the number of frames used is also left up to the designer. It is possible that several frames could be analyzed with associated motion analysis as well, to ensure the highest accuracy of the fore/back ground classification. The use of the nearest neighbor is not limited to four neighbors. The selection of

these specifics is left to the designer based upon the computational power of the system and the requirements of the final image.

Similarly, while the above process relies upon anisotropic diffusion for the refinement of classification, other types of refinements are available, such as  
5 morphological filtering, as mentioned above.

Application of this invention results in several options for users. A video conference participant can shield the actual background of the room from those at the receiving end of the image, for privacy or security reasons.

A Web publisher can generate transparent images in GIF format much  
10 more quickly than presently possible. Current techniques involve a pixel by pixel designation by the user to identify foreground and background pixels, a painstaking and tedious process. These same techniques are required when consumers using digital cameras want to crop and move objects in their digital images, whether video or still. These problems are eliminated by the application  
15 of this invention.

Thus, although there has been described to this point a particular embodiment for a method to perform background replacement, it is not intended that such specific references be considered as limitations upon the scope of this invention except in-so-far as set forth in the following claims.

WHAT IS CLAIMED IS:

1. A method for background replacement in image capture systems, comprising the steps of:
  - a) recording a background of an image with no foreground object with an  
5 image capture device;
  - b) using said image capture device to capture an input image;
  - c) classifying each pixel in said input image as a foreground pixel or a  
background pixel;
  - d) refining said classification to ensure proper classification;
  - 10 e) replacing said background pixels with pixels from a different background,  
wherein said replacing is performed with feathering; and
  - f) producing an output image comprised of said foreground pixels and said  
pixels from a different background.
2. The method as claimed in claim 1 where the refining step is performed in the  
15 normalized RGB chromatic color space.
3. The method as claimed in claim 1 wherein the refining step is performed in  
YCbCr color space.
4. The method as claimed in claim 1 wherein said image comprises one frame  
of video data.
- 20 5. The method as claimed in claim 1 wherein said image comprises more than  
one frame of video data.
6. The method as claimed in claim 1 wherein said image comprises a still  
image.

7. The method as claimed in claim 1, wherein said refining step is performed with anisotropic diffusion.
8. The method as claimed in claim 1, wherein said refining step is performed with morphological filtering.
- 5 9. The method as claimed in claim 1, wherein said output image is a video image.
10. The method as claimed in claim 1, wherein said output image is a still image.

65070 6875260

## ABSTRACT

A method for background replacement. The method takes an input image of one or more frames of video, or a still image, and performs an initial classification of the pixels (14) as foreground or background pixels. The classification is refined (16) using one of several techniques, including anisotropic diffusion or morphological filtering. After the refined classification is completed, a feathering process (18) is used to overlay the foreground pixels from the original image on the pixels of the new background, resulting in a new output image (20).

10

SECRET




Figure 1


ATTORNEY'S DOCKET NO.

SLA0095

**APPLICATION FOR UNITED STATES PATENT  
DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I declare that my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor if only one name is listed below, or an original, first and joint inventor if plural inventors are named below, of the subject matter which is claimed and for which a patent is sought on the invention entitled as set forth below, which is described in the attached specification; that I have reviewed and understand the contents of the specification, including the claims, as amended by any amendment specifically referred to in the oath or declaration; that no application for patent or inventor's certificate on this invention has been filed by me or my legal representatives or assigns in any country foreign to the United States of America; and that I acknowledge my duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, section 1.56;

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

<b>TITLE OF INVENTION:</b>		
<b>METHOD OF VIDEO BACKGROUND REPLACEMENT WITHOUT A BLUE SCREEN</b>		
<b>POWER OF ATTORNEY:</b> I HEREBY APPOINT THE FOLLOWING ATTORNEYS TO PROSECUTE THIS APPLICATION AND TRANSACT ALL BUSINESS IN THE PATENT AND TRADEMARK OFFICE CONNECTED THEREWITH:  Julie L. Reed, Registration No. 35,349		
<b>SEND CORRESPONDENCE TO:</b>	Julie L. Reed Sharp Labs of America 5750 NW Pacific Rim Blvd. Camas, WA 98607	<b>DIRECT TELEPHONE CALLS TO:</b>
<b>NAME OF INVENTOR: (1)</b>	<b>NAME OF INVENTOR: (2)</b>	<b>NAME OF INVENTOR: (3)</b>
Richard J. Qian		
<b>RESIDENCE &amp; POST OFFICE ADDRESS:</b>	<b>RESIDENCE &amp; POST OFFICE ADDRESS:</b>	<b>RESIDENCE &amp; POST OFFICE ADDRESS:</b>
2844 NW 44th Ave. Camas, WA 98607		
<b>COUNTRY OF CITIZENSHIP:</b>	<b>COUNTRY OF CITIZENSHIP:</b>	<b>COUNTRY OF CITIZENSHIP:</b>
China		
<b>SIGNATURE OF INVENTOR:</b>	<b>SIGNATURE OF INVENTOR:</b>	<b>SIGNATURE OF INVENTOR:</b>
		
<b>DATE:</b>	<b>DATE:</b>	<b>DATE:</b>
1/4/99		